



C-Bear Bottom Bracket Chart

Step 1

Step 2

Step 3

A = ATB/MTB
AC = MTB-Cyclocross
C = Cyclocross
R = Race

		Threaded			BB386	BBRight Cervelo Factor	OSBB 61 (carbon) Specialized	Pressfit30 (PF30)	PF30A Cannondale	BB30A Cannondale	BB30	PressFit (BB86/BB92)	T47	BB90/95 Trek	
		BSA Road	BSA MTB	ITA											
		BB shell Dmm			46	46	46	46	46	42	42	41	68(Road)	37	
		BB shell WIDTH mm			68	73	70	86.5(Road)	79(Road)	61(Road)	68(Road)	73(MTB)	86.5(Road)	68(Road)	90(Road)
		Crankset													
Spindle diameter 24 mm	Shimano HTII Rotor Face X-Type Rotor 3D, Agilis, Rex3														
	FSA Mega Exo														
Spindle diameter 24-22 mm	SRAM / Truvativ GXP														
Spindle diameter 25 mm	Campagnolo UT/ PT														
Spindle diameter 30 mm	Campagnolo OT FSA EVO386 THM Clavicula ZIPP Vumaquad SRM Origin														
	Rotor : 3D+ / 3DF Rex 1 / Rex 2 Inpower Aldhu / Vegast / Kapic SRAM Quarq Dzero Easton EC90 Hope FSA EVO392 Race Face NEXT														
	FSA BB30, SRAM BB30 Cannondale Hollowgram														
	Specialized - Fact														
Spindle diameter 28.99 mm	DUB Sram RED eTap AXS Sram Eagle Sram Eagle AXS														

Copyright © C-bear. All Rights Reserved.

Pulleys										
	•full ceramic •hybrid	•hybrid	•full ceramic	•full ceramic	•hybrid	•hybrid	•hybrid	•hybrid	•full ceramic •hybrid	T47-30-86-R T47-30-86-C
	PULL ALU SHI/SRAM PULL ALU SHI/SRAM FC	PULL CAR SHI/SRAM	PULL DEL SHI/SRAM PULL DEL SHI/SRAM FC	PULL TIT SHI/SRAM PULL TIT SHI/SRAM FC	PULL DEL XX1	PULL ALU EAGLE	PULL DEL AXE	PULL DEL AXE	PULL DEL CAM12 PULL DEL CAM12 FULL	Also available for DUB DUB-T47-86-R DUB-T47-86-C
Wheel bearings	Too many to list. Please provide bearing code or dimension and quantity									